

Model SMT-999

File Number: E526198



COMPANY

Anhui Surmount New Materials Co Ltd
Wei 2 Rd, Area C, Laian County Industrial park, chuzhou, anhui
chuzhou, Anhui 239500 China

MODEL INFO

SMT-999
Silicone "Room Temperature Vulcanizing" (RTV), furnished as two liquid components

FLAMMABILITY PROPERTIES	额定值	测试方法
Flammability		ANSI/UL 94
2.4 mm, Color: WT, BK	V-0	
7.0 mm, Color: WT, BK	V-0	
ISO/IEC FLAMMABILITY PROPERTIES	额定值	测试方法
Flammability		IEC 60695-11-10
2.4 mm, Color: WT, BK	V-0	
7.0 mm, Color: WT, BK	V-0	
THERMAL PROPERTIES	额定值	测试方法
Relative Thermal Index - Electrical Strength		UL 746B
2.4 mm	105 °C	
7.0 mm	105 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
2.4 mm	105 °C	
7.0 mm	105 °C	

Relative Thermal Index - Mechanical Strength		UL 746B
2.4 mm	105 °C	
7.0 mm	105 °C	

Report Date: 2024-12-19

并不是所有出现在本数据库中的公司名称和产品都满足了UL 跟踪检验服务的要求。只有带有 UL 标志的产品，才应该被视为经过UL认证，并满足UL 跟踪检验服务的要求。注意查看产品上的标志。

UL 允许在线认证目录中所含材料的复制遵循以下条件：1.指南信息、装配、构造、设计、系统和/或认证（文件）必须在不篡改任何数据（或图纸）的情况下完整且无误导性地呈现。2.“经 UL 允许从在线认证目录转载”声明必须出现在所摘取材料的邻近位置。此外，转载材料必须包含以下格式的版权声明：“©2024 UL LLC.”